

Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

#### Issue date 11/01/2015

Reviewed on 11/01/2015

Product Iden	ifier	
Product Num CAS Number 67-63-0 EC number: 200-661-7 Index numbe 603-117-00-0 Relevant iden No further rele		nd uses advised against:
Details of the Manufacturer NuGeneration 1155 Park Ave salesteam@n 1-888-996-843 Emergency te	Supplier of the Safety Data Sheet: /Supplier: Technologies, LLC (dba NuGenTec) nue, Emeryville, CA 94608	
	lentification of the substance or mixture:	
Classification	<i>of the substance or mixture:</i> 02 Flame	
Classification	of the substance or mixture: 02 Flame 225 Highly flammable liquid and vapor.	
Classification GHS Flam. Liq. 2 F Composition GHS Eye Irrit. 2 F	of the substance or mixture: 02 Flame 225 Highly flammable liquid and vapor.	
Classification GHS Flam. Liq. 2 H OFF Eye Irrit. 2 H STOT SE 3 H Label elemen GHS label elemen	of the substance or mixture: 02 Flame 225 Highly flammable liquid and vapor. 07 319 Causes serious eye irritation. 336 May cause drowsiness or dizziness. 55: ments is classified and labeled according to the G	lobally Harmonized System (GHS).
Classification GHS Flam. Liq. 2 H Flam. Liq. 2 H GHS Eye Irrit. 2 H STOT SE 3 H Label elemen GHS label elemen GHS label elemen	of the substance or mixture: 02 Flame 225 Highly flammable liquid and vapor. 07 319 Causes serious eye irritation. 336 May cause drowsiness or dizziness. 55: ments is classified and labeled according to the G	lobally Harmonized System (GHS).
Classification GHS Flam. Liq. 2 H Flam. Liq. 2 H GHS Eye Irrit. 2 H STOT SE 3 H Label elemen GHS label elemen GHS label elemen	of the substance or mixture: D2 Flame 225 Highly flammable liquid and vapor. 07 319 Causes serious eye irritation. 336 May cause drowsiness or dizziness. 5: ments is classified and labeled according to the G rams:	lobally Harmonized System (GHS).
Classification GHS Flam. Liq. 2 H Flam. Liq. 2 H GHS Eye Irrit. 2 H STOT SE 3 H Label elemen GHS label ele The substance Hazard pictos	of the substance or mixture: D2 Flame 225 Highly flammable liquid and vapor. 27 319 Causes serious eye irritation. 336 May cause drowsiness or dizziness. 5: ments is classified and labeled according to the G rams: 207	lobally Harmonized System (GHS).
Classification GHS Flam. Liq. 2 F Flam. Liq. 2 F GHS Eye Irrit. 2 F STOT SE 3 F Label elemen GHS label ele The substance Hazard pictos GHS02 GHS Signal word:	of the substance or mixture: D2 Flame 225 Highly flammable liquid and vapor. 27 319 Causes serious eye irritation. 336 May cause drowsiness or dizziness. 5: ments is classified and labeled according to the G rams: 207	lobally Harmonized System (GHS).





OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/01/2015

Trade name: Isopropyl Alcohol

Reviewed on 11/01/2015

· Hazard statements: Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves / eye protection / face protection. Wear eye protection / face protection. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · Unknown acute toxicity: 0 % of the mixture consists of component(s) of unknown toxicity. · Classification system: • NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1FIRE 3 Fire = 3Reactivity = 0REACTIVITY 0 · Hazard(s) not otherwise classified (HNOC): None known

## 3 Composition/Information on Ingredients

- · Chemical characterization: Substance
- · CAS No. Description
- 67-63-0 Isopropyl alcohol
- Identification number(s)
- EC number: 200-661-7

(Contd. on page 3)

US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/01/2015

Reviewed on 11/01/2015

Trade name: Isopropyl Alcohol

· Index number: 603-117-00-0

#### 4 First-Aid Measures

- · Description of first aid measures:
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse opened eye for at least 15 minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If swallowed and symptoms occur, consult a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed: No further relevant information available.
- Indication of any immediate medical attention and special treatment needed: No further relevant information available.

#### 5 Fire-Fighting Measures

- · Extinguishing media:
- Suitable extinguishing agents: CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture: No further relevant information available.
- Advice for firefighters:
- · Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

## 6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
Environmental precautions: Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up: Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Dispose of the collected material according to regulations.
Reference to other sections: See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/01/2015

Page 4/11

US

Trade name: Isopropyl Alcohol

## 7 Handling and Storage

- · Handling
- Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Protect from heat.
   Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities:
- · Storage
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- No further relevant information available.. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.
- Specific end use(s): No further relevant information available.

#### 8 Exposure Controls/Personal Protection

· Additional information about design of technical systems: No further data; see section 7.

## · Control parameters:

· Components with occupational exposure limits:		
67-6	63-0 Isopropyl alcohol	
PEL	Long-term value: 980 mg/m³, 400 ppm	
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
TLV	/ Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI	
· Ingr	redients with biological limit values:	
67-6	63-0 Isopropyl alcohol	
BEI	40 mg/L urine end of shift at end of workweek Acetone (background, nonspecific)	
· Ada	litional information: The lists that were valid during the creation of this SDS were	e used as basis.
· Pers · Gen The	<b>posure controls:</b> sonal protective equipment: neral protective and hygienic measures: usual precautionary measures for handling chemicals should be followed. op away from foodstuffs, beverages and feed.	(Contd. on page 5)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

#### Issue date 11/01/2015

Trade name: Isopropyl Alcohol

Reviewed on 11/01/2015

Immediately remove all soiled and contaminated clothing and wash before reuse. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Breathing equipment: Not required.
- · Protection of hands: Not required.
- · Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- · Penetration time of glove material: Not applicable.
- · Eye protection:



Tightly sealed goggles

## 9 Physical and Chemical Properties

- · Information on basic physical and chemical properties
- · General Information

-89.5 °C (-129 °F) 83 °C (181 °F) 12 °C (54 °F) Not applicable. 456 °C (853 °F)
Not determined. Not determined.
Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
2 Vol % 12 Vol %
42 hPa (32 mm Hg)



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/01/2015

Reviewed on 11/01/2015

Trade name: Isopropyl Alcohol			
<ul> <li>Vapor density:</li> <li>Evaporation rate:</li> </ul>	Not determined. Not determined.		
<ul> <li>Solubility in / Miscibility with: Water @ 20 °C (68 °F):</li> </ul>	1 g/l		
· Partition coefficient (n-octanol/w	ater): Not determined.		
· Viscosity:			
Dynamic @ 20 °C (68 °F):	2.43 mPas		
Kinematic:	Not determined.		
Organic solvents:	100.0 %		
VOC content:	100.0 %		
· Other information:	No further relevant information available.		

## 10 Stability and Reactivity

· Reactivity: No further relevant information available.

- · Chemical stability: Stable under normal conditions.
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions: No dangerous reactions known.
- Conditions to avoid: Heat, flame and ignition sources.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological Information

· Information on toxicological effects:

· Acute toxicity:

· LD/LC50 values	that are	relevant for	classification:
------------------	----------	--------------	-----------------

#### 67-63-0 Isopropyl alcohol

Oral	LD50	5045 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)
	LC50/96 hours	9640 mg/l (Pimephales)

## Primary irritant effect:

• On the skin: No irritating effect.

· On the eye: Irritating effect.

· Additional toxicological information:

#### · Carcinogenic categories:

· IARC (International Agency for Research on Cancer):

67-63-0 Isopropyl alcohol

· NTP (National Toxicology Program):

Substance is not listed.

(Contd. on page 7)

3

US



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/01/2015

Reviewed on 11/01/2015

Trade name: Isopropyl Alcohol

· OSHA-Ca (Occupational Safety & Health Administration):

Substance is not listed.

## 12 Ecological Information

- · Toxicity:
- · Aquatic toxicity:
- 67-63-0 Isopropyl alcohol
- EC50 6851 mg/l (Green algae)
  - 5102 mg/l (Water flea)
- · Persistence and degradability: No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or product that has not been neutralized to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment:
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects: No further relevant information available.

## 13 Disposal Considerations

- · Waste treatment methods:
- · Recommendation:

Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

## 14 Transport Information

- · UN-Number:
- · DOT, ADR, IMDG, IATA
- UN proper shipping name:
- · DOT
- · ADR
- · IMDG, IATA

UN1219

Isopropanol UN1219 Isopropanol ISOPROPANOL (ISOPROPYL ALCOHOL)

(Contd. on page 8)



Issue date 11/01/2015

# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Reviewed on 11/01/2015

Trade name: Isopropyl Alcohol Transport hazard class(es): · DOT · Class: 3 Flammable liquids · Label: 3 · ADR · Class: 3 (F1) Flammable liquids 3 · Label: · IMDG, IATA · Class: 3 Flammable liquids 3 · Label: · Packing group: · DOT, ADR, IMDG, IATA  $\parallel$ · Environmental hazards: Not applicable. · Special precautions for user: Warning: Flammable liquids · Danger code (Kemler): 33 · EMS Number: F-E,S-D Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable. · Transport/Additional information: · DOT · Quantity limitations: On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · ADR · Excepted quantities (EQ): Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IMDG · Limited quantities (LQ): 1L Code: E2 · Excepted quantities (EQ): Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml (Contd. on page 9) us



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/01/2015

Trade name: Isopropyl Alcohol

· UN "Model Regulation":

UN 1219 ISOPROPANOL, 3, II

## 15 Regulatory Information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture:
- · SARA (Superfund Amendments and Reauthorization):
- · Section 355 (extremely hazardous substances):
- Substance is not listed.
- Section 313 (Specific toxic chemical listings):
- Substance is listed.
- · TSCA (Toxic Substances Control Act):
- Substance is listed.
- · California Proposition 65:
- · Chemicals known to cause cancer:
- Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females:
- Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males:
- Substance is not listed.
- · Chemicals known to cause developmental toxicity:
- Substance is not listed.
- · Carcinogenic categories:
- · EPA (Environmental Protection Agency):
- Substance is not listed.
- · TLV (Threshold Limit Value established by ACGIH):
- 67-63-0 Isopropyl alcohol
- NIOSH-Ca (National Institute for Occupational Safety and Health):
- Substance is not listed.
- · GHS label elements
- The substance is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms:



- · Signal word: Danger
- Hazard-determining components of labeling: Isopropyl alcohol
- Hazard statements: Highly flammable liquid and vapor.

(Contd. on page 10)

US

A4

Reviewed on 11/01/2015



OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

#### Issue date 11/01/2015

Reviewed on 11/01/2015

Trade name: Isopropyl Alcohol

Causes serious eve irritation. May cause drowsiness or dizziness. · Precautionary statements: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use explosion-proof electrical/ventilating/lighting/equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves / eye protection / face protection. Wear eve protection / face protection. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · National regulations: Non-Regulated Material State Right to Know: None of the ingredients are listed · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Date of preparation / last revision: 11/01/2015 / 1
- · Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 11)

<sup>-</sup>US



Safety Data Sheet (SDS) OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 11/01/2015

Reviewed on 11/01/2015

Page 11/11

US

Trade name: Isopropyl Alcohol

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent 2D50: Letral dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 \* \* Data compared to the previous version altered. SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106