

Water Guard Inc (wgi) SAFETY DATA SHEET

I. Product and Company Information							
Product Name(s):	Aqua Ammonia (15% - 19% as NH ₃)	Synonym:	Ammonia Solution				
Chemical Name:	Ammonium Hydroxide	1336-21-6					
Manufacturer's Name:		Emergency Contacts:					
Water Guard Inc.		After hours (PERS)1-800-633-8253					
P.O. Box 2226							
Wilson, N.C. 27894							
Customer Service: 1-800	0-872-7665						
Web Site <u>www.watergu</u>	lardinc.com						

II. Hazard Identification					
OSHA HCS / GHS Classification(s):			Hazard Statement(s):		
Acute Toxicity, Oral (Category 4)			Harmful if swallowed.		
Skin Corrosion (Categ	ory 1)		Causes severe skin burns.		
Serious Eye Damage (Category 1)		Causes serious eye damage.		
Specific Target Organ (Category 3)	Toxicity (Respin	ratory - single exposure) -	May cause respiratory irritation.		
Acute Aquatic Toxicity	v (Category 3)		Harmful to aquatic life.		
Signal Word:	Precautionar	y Statement(s):			
Danger	Prevention :	Wash affected body parts	thoroughly afterhandling.		
		Do not eat, drink, or smoke when using this product.			
		Wear eye and face protection.			
		Wear protective gloves and clothing.			
		Do not breathe mist, vapors, or spray.			
\sim		Avoid release to the envir	void release to the environment.		
	Response:		outh. Do not induce vomiting. Immediately seek		
		medical advice.			
			ediately all contaminated clothing. Rinse skin		
		with water.			
			sly with water for several minutes. Remove		
		^	and easy to do so. Continuerinsing.		
		IF INHALED: Remove victim to fresh air and keep comfortable for			
		breathing.			
		Collect spillage: See section	on VI - Accidental Release Measures.		
		For specific treatment: Se	e section IV - First Aid section.		

III. Composition / Information on Ingredients						
Chemical NameCAS Reg #'s%						
Ammonia (NH ₃)	7664-41-7	15 - 19				
Water	7732-18-5	Balance				

IV. First Aid Measures				
Eyes:	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Remove any contact lenses. Seek medical attention, if you feel unwell.			
Dermal / Skin:	Remove contaminated clothing and wash exposed area thoroughly with soap and water. Seek medical attention, if you feel unwell.			
Inhalation:	Move to fresh air immediately. If breathing is difficult, give oxygen. Seek medical attention, if you feel unwell.			
Ingestion:	If swallowed, DO NOT induce vomiting. Rinse mouth. Seek medical attention, if you feel unwell.			

V. Fire Fighting Measures							
NEDA Hagand Dating	Health (Blue)	lealth (Blue) Fire (Red) Reactivity (Yellow) Special Instructions (V					
NFPA Hazard Rating:	3	1	0	None			
NFPA Hazard Cla	ssification: 0 =	Least 1 =	Slight 2 = Moderate	3 = High 4 = Extreme			
Extinguishing Media:	Use extinguish	ing media ap	propriate for surround	ling fire (Not CO_2).			
Special Firefighting	Wear full protect	ctive clothing	and a self-contained bre	athing apparatus (SCBA) because			
Procedure:	toxic fumes are	emitted. Stop	flow if possible. Use wa	ater to keep fire-exposed containers			
	cool and to protect persons shutting off flow of liquid. For a serious leak, use fire hose						
	with a fog nozzle and plenty of water to absorb ammonia vapors.						
Unusual Fire and	At elevated temperatures, aqua ammonia will emit ammonia gas and possibly small						
Explosive Hazards:	amounts of nit	amounts of nitrogen oxides which have been classified as toxic. Presence of oil or					
	other combust	other combustible materials increases the fire hazard of ammonia gas. Ammonia					
	concentrations	concentrations in the range of 16-25% by volume in air can be ignited or caused to					
	explode if heat	ed to the auto	o-ignition temperature				

VI. Accidental Release Measures				
Precaution if Spilled or Released:	Steps should be taken to contain spilled liquids and prevent discharges to streams or sewer systems. Ventilate spill or leak area to disperse gas. Eliminate all sources of ignition. Stop flow if possible. If small spill, either allow it to vaporize or absorb the vapor in water. If large spill, spray the vapor cloud with water to reduce fire and fume hazard.			
Neutralizing Chemicals:	Neutralization with acid not recommended. Flush area with water.			

	VII. Handling and Storage				
Handling:	Handle all chemicals with respect. Keep separated from incompatible substances. Handle only with equipment, materials, and supplies specified by their				
	manufacturer as being compatible and appropriate for use with this product.				
Storage:	Storage in specially designated areas outside or in detached structure is preferred. Store inside only in a cool, well-ventilated area free from combustibles and away from all sources of ignition. Protect containers from corrosion and mechanical damage. Containers should have safety relief valves. Separate from other chemicals, particularly oxidizing gases, organic materials, chlorine, bromine, iodine, mercury, and acids. Post readily visible warning signs in the storage area listing emergency measures. Water hoses should be readily available to knock down vapors from spill.				

VI	VIII. Exposure Control / Personal Protective Equipment						
Component Work	Component Workplace Control Parameters:						
Components:	CAS-I	No.	Value	Parameters	Basis	5	
Ammonia NH ₃	7664	-41-7	TWA	25 ppm	as An	nmonia NH ₃ (ACGIH)	
Engineering Control	ls:					gineering controls to keep th spective threshold limit valu	
General Hygiene:			-	sonal hygiene af g, or using the to		ng this material, especially b	oefore eating,
Personal Protection	on Equ	lipment:	1				
Eye:		face piec	e. Do not	00		nless protected by a respira s they may trap fumes agains	
Skin:		The use of gloves, boots, and aprons impermeable to the specific material handled (for Ammonia, includes Butyl, Teflon, Neoprene, and Viton) is advised to prevent skin contact, possible irritation, and skin damage.					
Respiratory:		None required under normal conditions. When conditions warrant a respirator, use NIOSH approved respirator and cartridge for particulates and ammonia.					
Other Protective Ite	ms:	Where splash is possible, full chemically resistant protective clothing and boots are required. Ensure that eyewash stations and safety showers are proximal to the work-station location.				0	
		Health (Blue)	Flammability (Red)	Physical Hazard (Yellow)	PPE (White)
HMIS Classification:		3		1		0	See Above
Hazard Cla	assific	ation: 0 =	= Minima	l 1= Slight	2 = Mo	derate 3 = Serious 4 = S	evere

IX. Physical and Chemical Properties						
Physical State:	Liquid	pH:	>12			
Appearance:	Clear, colorless liquid	Molecular Weight:	35.05			
Odor:	Pungent odor	Odor Threshold:	1-50 ppm			
Specific Gravity:(H ₂ 0=1)	0.94 (15% Solution); 0.92 (19% Solution); @ 60°F (15.5°C)	Weight per Gallon:	7.87 (15% Solution); 7.74 (19% Solution); lbs @ 60°F (15.5°C)			
Vapor Density: (Air=1)	0.045 lb/cf @ 60°F (15.5°C)	Vapor Pressure:	276 mm Hg (19%) 629 mm Hg (29%) @ 77°F (25°C)			
Boiling Point: at 14.7 psia	86°F - 138°F (30°C -58.9°C)	Freezing/Melting Point:	-106°F (-77°C)			
Lower Explosive Limit:	16% by volume Ammonia gas	Upper Explosive Limit:	25% by volume Ammonia gas			
Flash Point:	N/A	Auto ignition Temp:	1,204 °F (651 °C) (vapor)			
Solubility in water:	100%					

X. Stability and Reactivity Data					
Chemical Stability:	Product is stable under normal or expected use.				
Conditions To Avoid:	Heat, sunlight, incompatibles, sources of ignition.				
Incompatible Materials:	Corrosive to copper, brass, silver, zinc, aluminum alloys, and galvanized steel. Immediately boils when mixed with acids and is dangerous. Forms explosive compounds with calcium hypochlorite, bleaches, gold, mercury, silver, chlorine, and other halogens.				

Hazardous products of	Burning may produce ammonia and nitrogen oxides.
Decomposition:	

XI. Toxicological Information							
Routes of Entry:	es of Entry: \square Eyes \square Skin \square Ingestion \square Inhalation						
Sign and symptom	s of Expos	ure:	Burning of the eyes, conjunctivitis, skin irritations, swelling of the eyelids and lips, dry red mouth and tongue, burning in the throat, and coughing. In more severe cases of exposure, difficulty in breathing, signs and symptoms of lung congestion, and, ultimately, death from respiratory failure due to pulmonary edema may occur.				
Eye Contact:			Vapor is	irritating	g to the eyes. Liquic	l will cause burn	S.
Ingestion:			Ingestion causes burning pain in mouth, throat, stomach, and thorax, constriction of throat, and coughing. This is soon followed by vomiting of blood or by passage of loose stools containing blood. Ingestion of 3-4 ml may be fatal.				
Skin Contact:	Ammonia absorption: Because if its alkalinity and water solubility, tends to break down and disrupt the outer cell layers, permitting rapid penetration. Even so, ammonia is not a systemic poison and the effects will be limited to local effects. Contact: Causes smarting of the skin and first-degree burns on short exposure. May cause second-degree burns on long exposure.						
Inhalation:	Ammonia vapors are highly irritating to throat at approximately 400 ppm. Causes edema, dyspnoea, bronchospasm, chest pain, pink frothy sputum. Inhalation of 500 ppm Ammonia considered immediately dangerous to life and health (OSHA).						
Carcinogenicity:	NPT	Not List	ed	IARC	Not Listed	OSHA	Not Regulated
Ingredient Name:			Species		Test	Period	Results
Ammonium Hydrox	ide		Rat		350 mg/kg	oral	LD50
Comments:							

XII. Ecological Information					
Ingredient Name:		Species	Test	Period	Results
Ammonium Hydro	xide	Daphnia magna	32 mg/L	50 hrs	LC50
Comments:	Ammonia dissipates relatively quickly in ambient air and rapidly returns to the soil via combination with sulfate ions or washout by rainfall. Ammonia strongly adsorbs to soil, sediment particles, and colloids in water under aerobic conditions. Biodegradation of ammonia to nitrate occurs in water under aerobic conditions which results in a biological oxygen demand (BOD).				

XIII. Disposal Considerations		
Waste Disposal:	Always dispose of material in accordance with local, state, and federal regulations.	

XIV. Transportation Information					
Proper Shipping Name:	Ammonium Hydroxide, with more than 10% but not more than 35% as ammonia.				
DOT Classification:	8				
Identification Number:	UN 2672	Packing Group:	III	Other Labels:	Corrosive
Comments:					

XV. Regulatory Information					
Inventory Status: US R			egulations:		
U. S. TSCA	Yes	SARA 302 TPQ	500 lbs as ammon	ia NH3	
Europe EINECS	Yes	SARA 304 RQ	100 lbs as ammon	ia NH3	
Canadian DSL	Yes	SARA 313 List	Listed		
Japan ENCS	Yes	CERCLA (RQ)	1,000 lbs for pure a	ammonium hydroxide	
Korean KECI	Yes	RCRA 261.33	Not Listed		
Philippines PICCS	Yes	CAA-112r (RMP)	20,000 lbs as amm	nonia NH3 (Solution of	greater than 20%)
Australian AICS	Yes				
		SARA 311/312	🛛 Acute 🖂 Chron	ic 🖂 Fire 🔀 Release o	of Pressure 🗌 Reactive
International Regulations:				Other Regulations:	
Canada WHMIS	E	Corrosive		California PROP 65	No
EINECS	231-635-3	as Anhydrous Ammonia			
EINECS	215-647-6	as Aqua Ammonia			

XVI. Other Information			
NSF Certification:	Aqua Ammonia packaged is Wilson, NC NSF-60 certified. Maximum use in potable		
	water is 10 mg/L.		
Other:			
Revision Notes:			

IMPORTANT

Although the information contained is offered in good faith, SUCH INFORMATION IS EXPRESSLY GIVEN WITHOUT ANY WARRANTY (EXPRESS OR IMPLIED) OR ANY GUARANTEE OF ITS ACCURACY OR SUFFICIENCY and is taken at the user's sole risk. User is solely responsible for determining the suitability of use in each particular situation. WGI specifically DISCLAIMS ANY LIABILITY WHATSOEVER FOR THE USE OF SUCH INFORMATION, including without limitation any recommendation which user may construe and attempt to apply which may infringe or violate valid patents, licenses, and/or copyright.